

IN THE CLAIMS:

1-17. (cancelled)

18. (formally amended) In a data communication device comprising a communication module, a communication control method comprising the steps of:

- detecting a disruption of communication while the communication is in progress by the communication module;
- determining, based on a cause of the disruption, whether or not the disrupted communication is restorable;
- when the disrupted communication is determined not restorable, reporting the disruption to the communication module;
- if the disrupted communication is determined restorable, disguising the disruption from the communication module while monitoring if the disrupted communication becomes ready for restoration; and
- reporting the disruption to the communication module if the disrupted communication does not become ready for restoration within a period of time, whereas, if the disrupted communication becomes ready for restoration within the period of time, reestablishing the disrupted communication to resume the communication without reporting the disruption to the communication module.

19. (formally presented) A method according to claim 18, wherein the data communication device is selected from a group consisting of a portable computer, a server and a facsimile.

20. (formally amended) A method according to claim 18, wherein monitoring if the disrupted communication becomes ready for restoration comprising requesting a communication adapter to diagnose a network at regular intervals and waiting for a diagnostic result from the communication adapter.

21. (cancelled)

22. (formally presented) A method according to claim 18, wherein the disrupted communication is determined restorable if the disruption is caused by a traffic congestion in a network.

23. (formally presented) A method according to claim 18, wherein the data communication device is communicating wirelessly with a corresponding data communication device.

24. (formally amended) A method according to claim 23, wherein the disrupted communication is determined restorable if the disruption is caused by either the data communication device or the corresponding data communication device, or both, being temporarily out of reach of a radio signal.

25. (formally amended) A method according to claim 18, wherein disguising the disruption from the communication module comprises not reporting the disruption to the communication module as if the disruption never happened and let the communication module repeat communication operations that it was performing before the disruption.

26. (formally presented) In a data communication device that communicates with a corresponding data communication device over a network, a communication control module comprising:

- a communication control that controls data communication with the corresponding data communication device under direction of the data communication device;

- a network analyzer that detects a disruption of the data communication and determines, based on a cause of the disruption, whether or not the disrupted data communication is restorable, wherein the network analyzer reports the communication disruption to the data communication device if it determines that the disrupted data communication is not restorable;

- a network monitor that monitors the network within a period of time to detect if the disrupted communication becomes ready for restoration; and

- a communication disruption management that disguises the communication disruption from the data communication device while the network monitor monitors the

network, wherein the communication disruption management reports the communication disruption to the data communication device if the network monitor fails to detect within the period of time that the disrupted communication becomes ready for restoration, whereas if the network monitor detects within the period of time that the disrupted communication becomes ready for restoration, the communication disruption management instructs the communication control, without reporting the disruption to the communication device, to reestablish the disrupted communication and resume the data communication.

27. (formally presented) A communication control module according to claim 26, wherein the data communication device is selected from a group consisting of a portable computer, a server and a facsimile.

28. (formally presented) A communication control module according to claim 26, wherein when monitoring the network, the network monitor causes a communication adapter to diagnose the network at regular intervals and waits for a diagnostic result from the communication adapter.

29. (formally presented) A communication control module according to claim 26, wherein the network analyzer determines that the disrupted communication is restorable if the disruption is caused by a traffic congestion in the network.

30. (formally presented) A communication control module according to claim 26, wherein the data communication device is communicating wirelessly with the corresponding data communication device.

31. (formally presented) A communication control module according to claim 30, wherein the network analyzer determines that the disrupted communication is restorable if the disruption is caused by either the data communication device or the corresponding data communication device, or both, being temporarily out of reach of a radio signal.

32. (formally presented) A communication control module according to claim 26, wherein when disguising the disruption from the data communication device, the communication disruption management does not report the disruption to the

communication device as if the disruption never happened and lets the data communication device repeat communication operations that it was performing before the disruption.